

Easy 209P WG-PG, PT

PRODUCT DESCRIPTION

Soft monomeric PVC self-adhesive printing media.

Face Material: 200 µm white gloss PVC

Adhesive:

Easy 209P WG-PT: Emulsion acrylic permanent transparent

Easy 209P WG-PG: Emulsion acrylic permanent grey

Liner: Clay coated 120 g/sqm

TYPICAL USE

Short term indoor and outdoor advertising for promotional applications on flat surfaces.

Displays, shop windows, Point of Sale.

PROCESSING

Especially designed for solvent based, eco-solvent, mild solvent, Latex and UV inkjet printing on wide format printing equipment. To achieve optimal protection and durability, Easy 209 P may be laminated with LF 8000 Series.

To achieve the best possible print quality, please make sure that the correct ICC profiles or printer settings are used. Profiles can be obtained from our subsidiaries or distributors, or can be downloaded from: www.mactacgraphics.eu.

For further information on printing, application and removal, please refer to "TB 4.1 Guidelines on handling, converting and applying Mactac Digital media".

To ensure application suitability, always test the proposed construction under actual application and end-use conditions before going into full production.

SHELF LIFE

1 year when stored at 15 to 25°C and ± 50 % relative humidity (in the original packaging).

PHYSICAL PROPERTIES (TYPICAL VALUES)

Average Values Test Method

| Thickness | | |
|---|--------------------|---------|
| Face (microns) | 200 µm | ISO 534 |
| Adhesive data, 23°C (N/25 mm) | | |
| Peel adhesion on glass | | |
| 20 min. residence | 12 | FTM9 |
| 24 hour residence | 14 | FTM1 |
| Dimensional stability | | |
| Shrinkage (48 hours at 70°C applied on Aluminium) | Max. 0.2 mm | FTM14 |
| Temperature ranges | | |
| Minimum application temperature (°C) | + 10°C | |
| Service temperature range (°C) | - 20°C to + 70°C | |
| Certifications | | |
| Fire Classification | Self-extinguishing | |

EXPECTED DURABILITY

Central Europ Zone 1

| | | |
|-------------|---------------|------------|
| Unprocessed | Up to 2 years | ISO 4892-2 |
|-------------|---------------|------------|

Note : Exposure to severe temperatures, ultraviolet light, and/or conditions in Southern European countries, tropical, sub-tropical or desert regions will cause more rapid deterioration. This also applies to polluted areas, high altitudes and south-facing exposure.

DISCLAIMER

For more information on the durability and exposure please visit the "Mactac Technical Bulletin TB 7.5 Outdoor Durability of Mactac Graphics - Self-adhesive films" on the www.mactacgraphics.eu website.

Avery Dennison warrants that its Products meet its specifications. Avery Dennison gives no other express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of merchantability, fitness for any particular use and/or non infringement. All Avery Dennison products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purposes. The period of warranty is one (1) year from the date of shipment unless expressly provided otherwise in the product data sheet. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>. Avery Dennison's aggregate liability to Purchaser, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoices to Purchaser in respect of any occurrence or series of occurrences. In no circumstances shall Avery Dennison be liable to Purchaser for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.